

# Eco-Design-Regulation EU 2016/2281

Requirements for the documentation  
(Appendix 2 / Chapter 5 / Table 15)

## Product data

Unit	xtend.k/t 250 W
Type of liquefaction	W
Refrigerant/GWP	R410a / 2088

	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	7,13	---
Annual energy consumption	Q	21.861	kWh/a
Reduction factor C <sub>dc</sub> of chillers	C <sub>dc</sub>	---	---
Power regulation	---	variabel	---

## Parameter at full load and reference temperature at assessment point A

Rated refrigeration capacity	P <sub>A</sub>	21,05	kW
Rated power consumption	D <sub>A</sub>	5,13	kW
Energy efficiency ratio	EER <sub>DC,A</sub>	4,10	---

## Parameter at assessment point B

Declared cooling capacity	P <sub>B</sub>	19,64	kW
Declared power consumption	D <sub>B</sub>	3,56	kW
Declared energy efficiency ratio	EER <sub>DC,B</sub>	5,52	---

## Parameter at assessment point C

Declared cooling capacity	P <sub>C</sub>	18,24	kW
Declared power consumption	D <sub>C</sub>	2,56	kW
Declared energy efficiency ratio	EER <sub>DC,C</sub>	7,13	---

## Parameter at assessment point D

Declared cooling capacity	P <sub>D</sub>	16,84	kW
Declared power consumption	D <sub>D</sub>	2,11	kW
Declared energy efficiency ratio	EER <sub>DC,D</sub>	7,99	---