

# Eco-Design-Regulation EU 2016/2281

Requirements for the documentation  
(Appendix 2 / Chapter 5 / Table 15)

## Product data

<b>Unit</b>	xtend.k/t 350 W
Type of liquefaction	W
Refrigerant/GWP	R410a / 2088

	<b>Symbol</b>	<b>Value</b>	<b>Unit</b>
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	7,19	---
Annual energy consumption	Q	26.291	kWh/a
Reduction factor C <sub>dc</sub> of chillers	C <sub>dc</sub>	---	---
Power regulation	---	variabel	---

## Parameter at full load and reference temperature at assessment point A

Rated refrigeration capacity	P <sub>A</sub>	25,52	kW
Rated power consumption	D <sub>A</sub>	6,23	kW
Energy efficiency ratio	EER <sub>DC,A</sub>	4,10	---

## Parameter at assessment point B

Declared cooling capacity	P <sub>B</sub>	23,82	kW
Declared power consumption	D <sub>B</sub>	4,66	kW
Declared energy efficiency ratio	EER <sub>DC,B</sub>	5,11	---

## Parameter at assessment point C

Declared cooling capacity	P <sub>C</sub>	22,12	kW
Declared power consumption	D <sub>C</sub>	3,13	kW
Declared energy efficiency ratio	EER <sub>DC,C</sub>	7,07	---

## Parameter at assessment point D

Declared cooling capacity	P <sub>D</sub>	20,42	kW
Declared power consumption	D <sub>D</sub>	2,41	kW
Declared energy efficiency ratio	EER <sub>DC,D</sub>	8,48	---