

Eco-Design-Regulation EU 2016/2281

Requirements for the documentation
(Appendix 2 / Chapter 5 / Table 15)

Product data

Unit	xtend.k/t	600 W
Type of liquefaction		W
Refrigerant/GWP		R410a / 2088

	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	7,21	---
Annual energy consumption	Q	53.579	kWh/a
Reduction factor C _{dc} of chillers	C _{dc}	---	---
Power regulation	---	variabel	---

Parameter at full load and reference temperature at assessment point A

Rated refrigeration capacity	P _A	52,11	kW
Rated power consumption	D _A	12,54	kW
Energy efficiency ratio	EER _{DC,A}	4,15	---

Parameter at assessment point B

Declared cooling capacity	P _B	48,64	kW
Declared power consumption	D _B	8,89	kW
Declared energy efficiency ratio	EER _{DC,B}	5,47	---

Parameter at assessment point C

Declared cooling capacity	P _C	45,16	kW
Declared power consumption	D _C	6,18	kW
Declared energy efficiency ratio	EER _{DC,C}	7,30	---

Parameter at assessment point D

Declared cooling capacity	P _D	41,69	kW
Declared power consumption	D _D	5,19	kW
Declared energy efficiency ratio	EER _{DC,D}	8,03	---