

Eco-Design-Regulation EU 2016/2281

Requirements for the documentation
(Appendix 2 / Chapter 5 / Table 15)

Product data

Unit	xtend.k/t 150 A
Type of liquefaction	L
Refrigerant/GWP	R513A / 631

	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	5,15	---
Annual energy consumption	Q	17.062	kWh/a
Reduction factor C _{dc} of chillers	C _{dc}	---	---
Power regulation	---	variabel	---

Parameter at full load and reference temperature at assessment point A

Rated refrigeration capacity	P _A	11,87	kW
Rated power consumption	D _A	4,11	kW
Energy efficiency ratio	EER _{DC,A}	2,88	---

Parameter at assessment point B

Declared cooling capacity	P _B	11,07	kW
Declared power consumption	D _B	2,89	kW
Declared energy efficiency ratio	EER _{DC,B}	3,83	---

Parameter at assessment point C

Declared cooling capacity	P _C	10,28	kW
Declared power consumption	D _C	1,96	kW
Declared energy efficiency ratio	EER _{DC,C}	5,25	---

Parameter at assessment point D

Declared cooling capacity	P _D	9,49	kW
Declared power consumption	D _D	1,65	kW
Declared energy efficiency ratio	EER _{DC,D}	5,76	---