

Eco-Design-Regulation EU 2016/2281

Requirements for the documentation
(Appendix 2 / Chapter 5 / Table 15)

Product data

Unit	xtend 150
Type of liquefaction	W
Refrigerant/GWP	R513A / 631

	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	7,08	---
Annual energy consumption	Q	13.875	kWh/a
Reduction factor C _{dc} of chillers	C _{dc}	---	---
Power regulation	---	variabel	---

Parameter at full load and reference temperature at assessment point A

Rated refrigeration capacity	P _A	13,26	kW
Rated power consumption	D _A	3,21	kW
Energy efficiency ratio	EER _{DC,A}	4,13	---

Parameter at assessment point B

Declared cooling capacity	P _B	12,38	kW
Declared power consumption	D _B	2,05	kW
Declared energy efficiency ratio	EER _{DC,B}	6,03	---

Parameter at assessment point C

Declared cooling capacity	P _C	11,49	kW
Declared power consumption	D _C	1,69	kW
Declared energy efficiency ratio	EER _{DC,C}	6,78	---

Parameter at assessment point D

Declared cooling capacity	P _D	10,61	kW
Declared power consumption	D _D	1,34	kW
Declared energy efficiency ratio	EER _{DC,D}	7,94	---