

Eco-Design-Regulation EU 2016/2281

Requirements for the documentation
(Appendix 2 / Chapter 5 / Table 15)

Product data

Unit	xtend.k/t 350 A
Type of liquefaction	L
Refrigerant/GWP	R410a / 2088

	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	5,12	---
Annual energy consumption	Q	33.494	kWh/a
Reduction factor C _{dc} of chillers	C _{dc}	---	---
Power regulation	---	variabel	---

Parameter at full load and reference temperature at assessment point A

Rated refrigeration capacity	P _A	23,14	kW
Rated power consumption	D _A	8,68	kW
Energy efficiency ratio	EER _{DC,A}	2,66	---

Parameter at assessment point B

Declared cooling capacity	P _B	21,59	kW
Declared power consumption	D _B	5,97	kW
Declared energy efficiency ratio	EER _{DC,B}	3,62	---

Parameter at assessment point C

Declared cooling capacity	P _C	20,05	kW
Declared power consumption	D _C	4,15	kW
Declared energy efficiency ratio	EER _{DC,C}	4,84	---

Parameter at assessment point D

Declared cooling capacity	P _D	18,51	kW
Declared power consumption	D _D	2,93	kW
Declared energy efficiency ratio	EER _{DC,D}	6,32	---