

Eco-Design-Regulation EU 2016/2281

Requirements for the documentation
(Appendix 2 / Chapter 5 / Table 15)

Product data

Unit	xtend.k/t 900 A
Type of liquefaction	L
Refrigerant/GWP	R410a / 2088

	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	6,09	---
Annual energy consumption	Q	79.344	kWh/a
Reduction factor C _{dc} of chillers	C _{dc}	---	---
Power regulation	---	variabel	---

Parameter at full load and reference temperature at assessment point A

Rated refrigeration capacity	P _A	65,23	kW
Rated power consumption	D _A	22,80	kW
Energy efficiency ratio	EER _{DC,A}	2,86	---

Parameter at assessment point B

Declared cooling capacity	P _B	60,88	kW
Declared power consumption	D _B	15,07	kW
Declared energy efficiency ratio	EER _{DC,B}	4,04	---

Parameter at assessment point C

Declared cooling capacity	P _C	56,53	kW
Declared power consumption	D _C	9,95	kW
Declared energy efficiency ratio	EER _{DC,C}	5,68	---

Parameter at assessment point D

Declared cooling capacity	P _D	52,18	kW
Declared power consumption	D _D	6,61	kW
Declared energy efficiency ratio	EER _{DC,D}	7,89	---